

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An apparatus comprising:
 - a body casing having a plurality of surfaces;
 - an input keypad disposed on a first surface of said body casing to facilitate entry of alphanumeric data;
 - at least a first button disposed on a second surface of said body casing; and
 - complementary logic to
 - facilitate entry of alphanumeric data and user programmable phrases in encoded representations of a variable length encoding scheme using said at least first button, the variable length encoding scheme having a plurality of codes of various code lengths,
 - wherein the shortest code of the variable length encoding scheme
 - represents a first user ~~programmable-selectable~~ phrase comprising a plurality of alphanumeric characters, the first user selectable phrase being selected by a user from among a plurality of phrases for representation by the shortest code, said shortest code representing;
 - said first user ~~programmable-selectable~~ phrase in its entirety comprising one or more words, and
 - wherein the second shortest code of the variable length encoding scheme
 - represents a second user ~~programmable-selectable~~ phrase comprising a plurality of alphanumeric characters, the second user selectable phrase being selected by a user from among a plurality of phrases for representation by the second shortest code, said second shortest code

~~representing; said second user programmable-selectable phrase comprising one or more words in its entirety; and~~
facilitate the user in assigning the first user programmable-selectable phrase selected by the user to the shortest length-code of the variable encoding scheme and in assigning the second user programmable-selectable phrase selected by the user to the second shortest length-code of the variable encoding scheme.
~~-of the variable encoding scheme and in assigning the second user programmable phrase selected by the user to the second shortest length-code of the variable encoding scheme.~~

2. (Currently Amended) The apparatus of claim 1, wherein said apparatus further comprises a display, and said complementary logic further echoes on said display the first user selectable phrase in its entirety in response to input, through said at least first button, of said shortest code alphanumeric data or user programmable phrases represented by encoded representations representing said alphanumeric data and encoded representations directly representing said user programmable phrases entered using said at least first button.

3. (Currently Amended) The apparatus of claim 1, wherein said at least first button is optically associated with a light source, and said complementary logic further causes said light source associated with said at least first button to be energized to light said first button to visually echo the encoded representations of said variable length encoding scheme of letters, numbers or punctuations entered through said input keypad.

4. (Currently Amended) The apparatus of claim 1, wherein said apparatus further comprises a transceiver to send and receive signals, and an adapter interface to removably attach a device

capable of vibrating to said apparatus, and to vibrationally output alphanumeric data or user ~~programmable-selectable~~ phrases received through said transceiver, for touch comprehension, using said removably attached device capable of vibrating.

5. (Currently Amended) The apparatus of claim 4, wherein said alphanumeric data or user selectable or user programmable phrases are vibrationally outputted through vibrational manifestation of encoded representations of the variable length encoding scheme.

6.-8. (Cancelled)

9. (Currently Amended) The apparatus of claim 1, wherein said complementary logic further supports user specification of ~~said-user programmable-selectable~~ phrases having one or more words.

10. (Cancelled)

11. (Currently Amended) The apparatus of claim 1, wherein an alphanumeric character is selectable by a user for representation by a third code of said encoded representations comprise a code representing a punctuation~~the variable length encoding scheme, the alphanumeric character being~~ selected from a group of punctuations consisting of a space, a slash, a comma, a period, a question mark, a colon, a semi-colon, a left parenthesis, a right parenthesis, and an exclamation.

12. (Currently Amended) The apparatus of claim 11, wherein said third code representing the selected punctuation is one of

Selected Punctuation	Code
----------------------	------

/ (slash)	<i>dahditdahditdah</i>
, (comma)	<i>dahdahditditdah</i>
. (period)	<i>dahdahdahditdah</i>
? (question mark)	<i>ditdahditdah</i>
: (colon)	<i>ditdahdahditdah</i>
; (semicolon)	<i>ditdahditditdah</i>
! (exclamation)	<i>ditdahditdahdit</i>
((left parenthesis)	<i>ditditdahditdit</i>
) (right parenthesis)	<i>dahdahditdahdah</i>
space	<i>ditditditdit</i>
‘ (single quote)	<i>dahditdahdahdah</i>
“ (double quote)	<i>ditdahditdahdah</i>
- (hyphen)	<i>ditdahdahdahdit</i>
+ (plus sign)	<i>dahditditditdah</i>
= (equal sign)	<i>ditditdahdahdit</i>

13. (Currently Amended) The apparatus of claim 1, wherein an alphanumeric character is selectable by a user for representation by a third code of the variable length encoding scheme, the alphanumeric character being said encoded representations comprise a code representing a letter selected from a group of a letters and the third code consisting of

Letters	Custom Codes
E	<i>ditdit</i>
G	<i>dahdahdahdit</i>
H	<i>dahditdah</i>

I	<i>ditdahdah</i>
K	<i>ditdahditdit</i>
L	<i>dahdahdit</i>
M	<i>dahdahdahdah</i>
T	<i>dahdah</i>
W	<i>ditditdahdah</i>

14. (Currently Amended) The apparatus of claim 1, wherein said complementary logic further maps ~~said each of said entered variable length encode representation~~first shortest codens to ~~a correspondingsaid first word or phrase code of a fixed length binary representation scheme for representing alphanumeric data.~~

15. (Currently Amended) The apparatus of claim 1, wherein said apparatus further comprises at least an additional second button for use in conjunction with the first button to enter ~~direct encoded representations for~~a third code of the variable encoding scheme, wherein the third code is assigned to a third user programmable selectable word or phrases having one or more words~~a plurality of alphanumeric characters, the third code being input using at least said additional second button.~~

16.-17. (Cancelled)

18. (Previously Presented) The apparatus of claim 1, wherein said first and second surfaces are different surfaces of the body casing.

19. (Previously Presented) The apparatus of claim 18, wherein said first surface is a front surface of the body casing, and said second surface is a second surface of the body casing.

20. (Previously Presented) The apparatus of claim 1, wherein said first and second surfaces are the same surface of the body casing.

21. (Currently Amended) An apparatus comprising:

a transceiver to send and receive signals;

an adapter interface to removably attach a device capable of vibrating to said apparatus;

and

complementary logic in support of said transceiver and said adapter interface to

vibrationally output alphanumeric data and ~~user-programmable~~ user selectable

phrases having one or more words received via said transceiver through

vibrational manifestation of encoded representations of the received

alphanumeric data and ~~user-programmable~~ user selectable phrases for touch

comprehension, using the removably attached device capable of vibrating,

wherein the vibrationally manifested encoded representations are

~~representations~~ codes of a variable length encoding scheme, the variable

length encoding scheme having a plurality of codes of various code lengths,

wherein

the shortest code of the variable length encoding scheme represents a first

~~user programmable-selectable phrase, the first user selectable phrase~~

being selected by a user for representation in its entirety by said

shortest code, and said first user programmable-selectable phrase

comprising one or more words a plurality of alphanumeric characters,

and

the second shortest code of the variable length encoding scheme represents

a second user ~~programmable-selectable~~ phrase selected by a user for

representation in its entirety by said second shortest code, and said
second user programmable-selectable phrase comprising one or more
words a plurality of alphanumeric characters, and
 facilitate the user in assigning the first user ~~programmable-selectable~~ phrase
 selected by the user to the shortest length code of the variable encoding scheme
 and in assigning the second user ~~programmable-selectable~~ phrase selected by
 the user to the second shortest length code of the variable encoding scheme,
wherein said first user selectable phrase and said second user selectable phrase
are selectable by the user from among a plurality of phrases.

22. (Currently amended) The apparatus of claim 21, wherein said apparatus further comprises
 a display, and said complementary logic further supports echoing on said display said
 alphanumeric data or user ~~programmable-selectable~~ phrases received through said transceiver.

23.-26. (Cancelled)

27. (Currently Amended) The apparatus of claim 21, wherein said encoded representations
 comprise a code representing a punctuation selected from a group of punctuations consisting of a
space, a slash, a comma, a period, a question mark, a single quote, a double quote, a hyphen, a
 colon, a semi-colon, a left parenthesis, a right parenthesis, and an exclamation.

28. (Previously Presented) The apparatus of claim 27, wherein said code representing the
 selected punctuation is a selected one of

Selected Punctuation	Code
/ (slash)	<i>dahditdahditdah</i>

, (comma)	<i>dahdahditditdah</i>
. (period)	<i>dahdahdahditdah</i>
? (question mark)	<i>ditdahditdah</i>
: (colon)	<i>ditdahdahditdah</i>
; (semicolon)	<i>ditdahditditdah</i>
! (exclamation)	<i>ditdahditdahdit</i>
((left parenthesis)	<i>ditditdahditdit</i>
) (right parenthesis)	<i>dahdahditdahdah</i>
space	<i>ditditditdit</i>
' (single quote)	<i>dahditdahdahdah</i>
" (double quote)	<i>ditdahditdahdah</i>
- (hyphen)	<i>ditdahdahdahdit</i>
+ (plus sign)	<i>dahditditditdah</i>
= (equal sign)	<i>ditditdahdahdit</i>

29. (Previously Presented) The apparatus of claim 21, wherein said encoded representations comprise a code representing a letter selected from a group of letters consisting of

Letters	Custom Codes
E	<i>ditdit</i>
G	<i>dahdahdahdit</i>
H	<i>dahditdah</i>
I	<i>ditdahdah</i>
K	<i>ditdahditdit</i>
L	<i>dahdahdit</i>

M	<i>dahdahdahdah</i>
T	<i>dahdah</i>
W	<i>ditditdahdah</i>

30. (Previously Presented) The apparatus of claim 21, wherein said alphanumeric data are received in fixed length binary representations of a fixed length character encoding scheme, and said complementary logic maps each of the received fixed length binary representations to a corresponding encoded representation of the variable length encoding scheme.

31. (Currently amended) An apparatus comprising:

a body casing having a plurality of surfaces;

an input keypad disposed on a first of said surfaces having a plurality of alphanumeric keys;

a light source;

at least a first button disposed on a second of said surfaces, optically associated with the light source; and

complementary logic in support of

entry, through the input keypad, of alphanumeric data and user programmable selectable phrases selected by ~~the a user for encoding~~, said user selectable ~~user programmable phrases having one or more words~~ being selectable by the user from among a plurality of phrases,

entry, using said first button, of alphanumeric data and user programmable selectable phrases through entry of encoded representations of the alphanumeric data and the user programmable phrases, wherein the encoded representations are ~~representations codes of~~ of a variable length encoding

scheme, the variable length encoding scheme having a plurality of codes of various code lengths,

wherein the shortest code of the variable length encoding scheme represents a first user programmable phrase selected by ~~a~~the user, said first user programmable phrase being represented in its entirety by the shortest code, wherein said first user programmable phrase comprises a plurality of alphanumeric characterse~~comprising one or more words~~, and

wherein the second shortest code of the variable length encoding scheme represents a second user programmable phrase ~~selected by a~~the user, said second user programmable phrase being represented in its entirety by the second shortest code, wherein said second user programmable phrase comprises a plurality of alphanumeric characterse~~comprising one or more words~~;

assignment of ~~one~~the first user ~~programmable-selectable~~ phrase selected by the user to the shortest length code of the variable encoding scheme, ~~and~~

~~in-assigning~~ment of the second user ~~programmable-selectable~~ phrase selected by the user to the second shortest length code of the variable encoding scheme, and

energizing of said light source to light said first button to visually echo said encoded representations of alphanumeric data and user programmable phrases entered through said input keypad.

32.-34. (Cancelled)

35. (Currently Amended) The apparatus of claim 31, wherein said complementary logic further supports user specification of ~~said-user programmable-selectable~~ phrases having one or more words.

36. (Currently Amended) The apparatus of claim 31, wherein said encoded representations comprise a code representing a punctuation selected from a group of punctuations consisting of a slash, a comma, a period, a question mark, a space, a single quote, a double quote, a hyphen, a plus sign, an equal sign, a colon, a semi-colon, a left parenthesis, a right parenthesis, and an exclamation.

37. (Previously Presented) The apparatus of claim 36, wherein said code representing the selected punctuation is a selected one of

Selected Punctuation	Code
/ (slash)	<i>dahditdahditdah</i>
, (comma)	<i>dahdahditditdah</i>
. (period)	<i>dahdahdahditdah</i>
? (question mark)	<i>ditdahditdah</i>
: (colon)	<i>ditdahdahditdah</i>
; (semicolon)	<i>ditdahditditdah</i>
! (exclamation)	<i>ditdahditdahdit</i>
((left parenthesis)	<i>ditditdahditdit</i>
) (right parenthesis)	<i>dahdahditdahdah</i>
space	<i>ditditditdit</i>
' (single quote)	<i>dahditdahdahdah</i>

“ (double quote)	<i>ditdahditdahdah</i>
- (hyphen)	<i>ditdahdahdahdit</i>
+ (plus sign)	<i>dahditditditdah</i>
= (equal sign)	<i>ditditdahdahdit</i>

38. (Previously Presented) The apparatus of claim 31, wherein said encoded representations comprise a code representing a letter selected from a group of letters consisting of

Letters	Custom Codes
E	<i>ditdit</i>
G	<i>dahdahdahdit</i>
H	<i>dahditdah</i>
I	<i>ditdahdah</i>
K	<i>ditdahditdit</i>
L	<i>dahdahdit</i>
M	<i>dahdahdahdah</i>
T	<i>dahdah</i>
W	<i>ditditdahdah</i>

39. (Previously Presented) The apparatus of claim 31, wherein said alphanumeric data are entered in fixed length binary representations of a fixed length character encoding scheme, and said complementary logic maps each of the entered fixed length binary representations to a corresponding encoded representation of the variable length encoding scheme.

40. (Previously Presented) The apparatus of claim 31, wherein said first and second surfaces are different surfaces of said body casing, and said light source comprises one or more light emitting diodes (LED) proximally disposed with the first button.

41-46 (Cancelled)

47. (Currently Amended) In a wireless mobile phone, a method comprising:

receiving encoded representations of a variable length encoding scheme of alphanumeric data and user programmable phrases having one or more words, said encoded representations entered using at least a first button disposed on a top or side surface of the mobile phone, said variable length encoding scheme comprising a plurality of codes of various code lengths,

wherein the shortest code of the variable length encoding scheme represents a first user programmable phrase ~~selectable~~selected by a user ~~for association with said shortest code~~, said first user programmable phrase comprising ~~one or more words~~a plurality of alphanumeric characters, and

wherein the second shortest code of the variable length encoding scheme represents a second user programmable phrase ~~selectable~~selected by a user ~~for association with said second shortest code~~, said second user programmable phrase comprising ~~one or more words~~a plurality of alphanumeric characters, and

~~wherein the shortest code represents the first user programmable phrase in its entirety, and the second shortest code represents said second user programmable phrase in its entirety,~~

and

said mobile phone also having an input keypad disposed on a front surface to facilitate entry of alphanumeric data; ~~and~~

electrically generating, in response to entry of said shortest code using said at least a first button, a electrically generating signals corresponding to a fixed length digital representations of said alphanumeric data or first user programmable-programmable phrases entered through entry of their variable length encoded representations of said variable length encoding scheme using said at least a first button, and

electrically generating, in response to entry of said second shortest code using said at least a first button, a signal corresponding to a fixed length digital representation of said second user programmable phrase.

48. (Previously Presented) The method of claim 47, wherein said method further comprises visually echoing on a display of said mobile phone said alphanumeric data or user programmable phrases entered through entry of their variable length encoded representations of said variable length encoding scheme using said at least a first button.

49. (Previously Presented) The method of claim 47, wherein each of said at least a first button is optically associated with a light source, and said method further comprises energizing said light source associated with said at least a first button to light said first button to visually echo the variable length encoded representations of said variable length encoding scheme of letters, numbers, punctuations, and user programmable phrases entered through said input keypad.

50. (Previously Presented) The method of claim 47, wherein said mobile phone further comprises an adapter interface to removably attach a capable of vibrating device to said mobile phone, and said method further comprises vibrationally outputting the variable length encoded representations of the alphanumeric data and user programmable phrases received through a

transceiver of said mobile phone for touch comprehension, using said removably attached capable of vibrating device.

51. (Currently Amended) A method of communication comprising:

placing a call to a callee using a wireless mobile phone;

communicating verbally with the callee using the wireless mobile phone; and

at selected moments of desired increased privacy during the call, communicating non-verbally ~~with to the callee~~ a user selected word or phrase, by entering an encoded representation of the user selected word or phrase ~~alphanumeric data through at least a first button disposed on a top or side surface of the wireless mobile phone, said user selected word or phrase comprising and user programmable phrases having one or more words to be transmitted to the callee and the in an encoded representation being a form code~~ in accordance with a variable length encoding scheme having a plurality of codes of various code lengths, using at least a first button disposed on a top or side surface of the wireless mobile phone, and sending the entered alphanumeric data and user programmable user selected word or phrases to the callee, said variable length encoding scheme comprising a plurality of codes of various code lengths,

wherein the shortest code of the variable length encoding scheme represents a first user

~~programmable phrase selected by a user~~ word or phrase, said first user

~~programmable selected word or phrase comprising one or more words~~ a plurality of

alphanumeric characters selected by the user, said first user selected word or

phrase being selected by the user to be encoded in its entirety by the shortest code,

and

wherein the second shortest code of the variable length encoding scheme represents a

~~second user programmable selected word or phrase selected by a user, said second~~

~~user programmable selected word or phrase comprising one or more words~~ a

plurality of alphanumeric characters selected by the user, said second user selected

word or phrase being selected to be encoded in its entirety by the second shortest code.

52. (Currently Amended) The method of claim 51, wherein the method further comprises mapping the variable length encoded representations of the ~~alphanumeric data and user programmable selected words or phrases~~ into corresponding conventional fixed length digital character set representations, in accordance with the variable length encoding scheme.

53-55 (Cancelled)

56. (Currently Amended) An apparatus comprising:
a transceiver to send and receive signals;
a body casing having a front surface and a side surface;
an input keypad disposed on said front surface of said body casing to facilitate entry of alphanumeric data and user programmable phrases having one or more words;
a first button disposed on said side surface of said body casing;
a second button disposed on said side surface of said body casing adjacent to said first button;

means coupled to the first and second buttons and to the transceiver to facilitate entry of alphanumeric data and user programmable phrases via corresponding code representations of a variable length coding scheme, using said first and second buttons, the variable length encoding scheme comprising a plurality of codes of various code lengths, and transmission of said alphanumeric data and user programmable phrases using said transceiver,

wherein the shortest code of the variable length encoding scheme represents a first user programmable phrase selected by a user, said first user programmable phrase being selectable by the user from among a plurality of user

programmable phrases and being represented in its entirety by the shortest code, and comprising one or more words a plurality of alphanumeric characters, and

wherein the second shortest code of the variable length encoding scheme represents a second user programmable phrase selected by a user, said second user programmable phrase being selectable by the user from among a plurality of user programmable phrases and being represented in its entirety by the second shortest code, and comprising one or more words a plurality of alphanumeric characters; and

means coupled to the input keypad to facilitate assignment of one or more of the user programmable phrases to the shortest length codes.

57. (Previously Presented) The apparatus of claim 56, wherein said apparatus further comprises a display, and said means further echoes on said display alphanumeric data or user programmable phrases represented by code representations entered using said first and second buttons.

58. (Previously Presented) The apparatus of claim 56, wherein said apparatus further comprises an adapter interface to removably attach a device capable of vibrating to said apparatus, and to vibrationally output alphanumeric data and user programmable phrases received through said transceiver for touch comprehension, using said removably attached capable of vibrating device.

59. (Previously Presented) The apparatus of claim 58, wherein said alphanumeric data and user programmable phrases are vibrationally outputted through vibrational manifestation of the code representations of the alphanumeric data and user programmable phrases.

60.-63. (Canceled)

64. (Currently Amended) In a wireless mobile phone, a method comprising:

receiving code representations of alphanumeric data and user programmable phrases, said user programmable phrases having one or more words and being selectable by the user from among a plurality of user programmable phrases, the code representations being entered using a first and a second button disposed on a top or side surface of the mobile phone, said mobile phone also having an input keypad disposed on a front surface to facilitate entry of said alphanumeric data or user programmable phrases, the variable length coding scheme having a plurality of codes of various code lengths,

wherein the shortest code of the variable length encoding scheme represents a first user programmable phrase selected by a user, the first user programmable phrase being represented in its entirety by the shortest code, wherein said first user programmable phrase including comprises a plurality of one or more words alphanumeric characters and, and

wherein the second shortest code of the variable length encoding scheme represents a second user programmable phrase selected by a user, the second user programmable phrase being represented in its entirety by the second shortest code, wherein said second user programmable phrase comprises a plurality of alphanumeric characters including one or more words; and

in response, electrically generating signals corresponding to digital representations of said alphanumeric data or user programmable phrases entered through entry of their code representations using said first and second buttons, and transmitting said alphanumeric data or user programmable phrases by electro-magnetically transmitting said generated signals.

65. (Previously Presented) The method of claim 64, wherein said method further comprises visually echoing on a display of said mobile phone said alphanumeric data or user programmable phrases entered through entry of their code representations using said first and second buttons.

66. (Previously Presented) The method of claim 64, wherein said mobile phone further comprises an adapter interface to removably attach a capable of vibrating device to said mobile phone, and said method further comprises vibrationally outputting alphanumeric data or user programmable phrases received through a transceiver of said mobile phone for touch comprehension, using said removably attached capable of vibrating device.

67-69 (Cancelled)